

PRATIKA 80-T MPS

AUTOMATIC PACKAGING MACHINE - CONTINUOUS SEALING (SEALING BAR 700MM X ∞) - FULLY ELECTRICAL AND SERVO-ASSISTED



DESCRIPTION

PRATIKA 80-T MPS: automatic wrapping machine. The acronym indicates the side seal device, the continuous welding that does not involve length limits to pack up to 4, 5, 6 meters. In addition to the equipment of the Center Sealing system, this new version of the machine, suitable to pack large sizes up to 700 mm wide x360 mm high, has been enhanced with a strong mechanical and electronic technological content.

Pratika 80-T MPS is an innovative **shrink wrap machine** that represents today a perfect synthesis of reliability, high performance, versatility and safety, to evolve once again the way to conceive automatic packaging machines with shrink films.

"Made in Italy with an international heart": all the **automatic wrapping machines** by minipack®-torre are produced entirely in the company's factories, with an inner heart made of the electrical and

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151

electronic components of a multinational corporation such as Schneider Electric.

PRATIKA 80-T MPS the most appreciated model of the new range of minipack®-torre automatic wrapping machines:

- Continuous welding system
- "Center Sealing" welding device
- Brushless servomotor by Schneider Electric
- Control logic by Schneider Electric PLC
- Electric power supply, no pneumatic connection needed
- Reduced energy consumption
- Compliance with CE regulations

TECHNICAL FEATURES

Electrical power supply	230V 50/60Hz 1Ph
MAX power installed	3 kW
Maximum current	13 A
Available dimensions of the sealing bars	700 mm x ∞
MAX product size (the maximum measurements cannot be used at the same time)	700x360 mm x L.∞
MAX Reel Dimensions (Ø x length)	Ø350x1000 mm
Infeed belt height	915 mm
Machine dimensions (guards open)	2785x3090x2280 mm
Machine dimensions (guards closed)	2785x2490x1770 mm
Type of power supply	Electrical power supply
Hourly output (based on the size of the product and the film used)	0-3000 p/h
Machine weight (Net/Gross)	1270/1500 kg (Pallets) 1270/1700 kg (Wooden crate)

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

minipack®-torre S.p.A.


Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



minipack®
THE ORIGINAL PIONEER

TECHNICAL DRAWING



TECHNICAL FEATURES

- Schneider Electric M258 PLC with 256 customisable and named programs
- Colour touch-screen control panel, 5.7 inch, 10 languages
- 2 Dual Core microprocessors (like 4) 2 x 32 bit
- USB Communication interface
- Schneider Electric brushless motor Drive
- Signalling of roll and film opening roller positioning on the set product height
- Micro-perforation device with film tensioning adjustment on the set product height
- New closed loop sealing bar actuation frame which balances efforts and makes motion smoother
- Self-adjustment of triangle and bar height on the set product height
- Sealing bar opening defined by product height, which may be set on the touch-screen control panel
- Belt speed (infeed/outfeed) adjusted by programmable Schneider Electric inverter model Altivar
- Electronic port (infeed/outfeed) for interfacing with supplementary unloading and loading belts
- Standard belts compliant with the strictest regulations in force in the food sector (FDA) and completely antistatic
- Full waste winder warning electronic device
- Possibility to match a heat-shrink tunnel.

EXCELLENT PRODUCTIVITY

- High sealing and productivity speed
- Electronically adjustable conveyor belt speed
- Electric belt approaching device (optional)
- Piece counter (day/life) and package length detection
- Option to package individual packages or sets of products.

EFFICIENT SEALING

- New Side Seal unit moved with a Stepper motor

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151

- Blade movement with Brushless motor
- Double sealing temperature adjustment, both on the longitudinal bar and on the Side Seal
- Automatic cross bar height may be set to the mm
- Sealing time and force adjustment (min/medium/max).

FOCUS ON SAFETY

- Machine protected by a cover with operator safety guard also including infeed and outfeed belt and roll support
- Opening hatches fitted with safety microswitch
- Control logic with operator safety
- Visible and acoustic machine stop alarm signal.

LEADING-EDGE TECHNOLOGY

- Biometric reader for data security (optional)
- Remote support (optional)
- Description of problem solution
- Remote control (optional).

EASE OF USE

- Lit working area
- Machine on adjustable wheels and feet
- Levelling spirit level
- Front and rear opening for easy access and servicing
- Personalised operator/maintenance technician utilisation mode.

ABSOLUTE FUNCTIONALITY

- Roll insertion at the rear
- Fitted with weights to adjust film tensioning
- High technology vertical photocell
- Electronic cycle counter
- General automatic and function control upon switch-on.